

Storminator™ Lite— Installation Manual



Storminator™ Lite— Installation Kit

- 1) Storminator™ Lite filter unit
- 2) Filter sock
- 3) Filter sock holder and inspection pipe
- 4) Media Bag
- 5) Top filter basket
- 6) Overflow protector
- 7) Overflow diverter
- 8) Leaf diverter
- 9) Filter gravel cannisters



Storminator™ Lite— Installation

- 1) If you are using the Storminator™ Lite installation kit refer to that instruction manual.
- 2) If using your own hardware ensure that the Storminator™ Lite is securely attached to the wall in an upright position with the leaf diverter above the unit.

Storminator™ Lite— Maintenance

To ensure performance, routinely check and clean the filter sock (replacing this when needed), gutters and leaf catchers of any detritus build up

Storminator™ Lite— Filling process

- 1) Add one of the pre-measured gravel cannisters to the filter unit, ensuring the gravel is level at the bottom of the unit.
- 2) Mix the media by rotating the media bag longitudinally 10 times.
- 3) Add the media bag to the filter unit ensuring that the top is level.
- 4) Add the last of the gravel canisters to the filter unit ensuring that the top is level.
- 5) Remove the overflow protector.
- 6) Install the top filter basket on the overflow pipe ensuring a snug fit against the level gravel surface.
- 7) Install the overflow diverter on the overflow pipe ensuring a tight fit.

